




# Fiesta

Fiesta is a durable furniture textile with many applications in both public and private environments. Now in updated color scheme.

Suitable for:  
Accessories, Boat/Caravan, Contract upholstery, Curtains and Drapery, Upholstery



Fabric Fiesta 10 Off  
white  
1008210



Fabric Fiesta 56 Linen  
1008256




Fabric Fiesta 16  
Beach  
1008216




Fabric Fiesta 26  
Beige melange  
1008226



Fabric Fiesta 6  
Tabacco  
1008206



Fabric Fiesta 47 Mole  
1008247




Fabric Fiesta 13 Lime  
1008213



Fabric Fiesta 3 Olive  
1008203



Fabric Fiesta 124  
Terra  
1008241



Fabric Fiesta 123  
Brick  
1008266



Fabric Fiesta 1 Red  
1008201




Fabric Fiesta 11  
Lipstick  
1008211



Fabric Fiesta 51  
Aubergine  
1008251




Fabric Fiesta 114 Pale  
rose  
1008221




Fabric Fiesta 85 Light  
purple  
1008291




Fabric Fiesta 88  
Orchid  
1008281



Fabric Fiesta 71 Plum  
1008271



Fabric Fiesta 122  
Lilac  
1008261



Fabric Fiesta 117  
Bottle green  
1008233



Fabric Fiesta 118  
Juniper  
1008242



Fabric Fiesta 22  
Petrol  
1008222



Fabric Fiesta 119  
Lagoon  
1008232



Fabric Fiesta 12  
Racing blue  
1008212




Fabric Fiesta 2 Ocean  
1008202



Fabric Fiesta 113 Ice  
1008267



Fabric Fiesta 89  
Greystoke  
1008257



Fabric Fiesta 4 Black  
1008204

|                                   |                                               |
|-----------------------------------|-----------------------------------------------|
| Width:                            | 148 cm ±2 cm cm                               |
| Content:                          | 100% Polyester                                |
| Weight (g/m²):                    | 420                                           |
| Roll length (m):                  | 35                                            |
| Type:                             | Piece Dyed                                    |
| Oeko-Tex Certificate No:          | 13.HCN.35063                                  |
| Fire class:                       | BS 5852-1 Source 0 & 1, Cal TB 117, EN 1021-1 |
| Martindale:                       | 70000 (ISO 12947-2)                           |
| Change of colour:                 | 3-4                                           |
| Pilling:                          | 4 (ISO 12945-2)                               |
| Colour fastness to rubbing - dry: | 4-5 (ISO 105-X12)                             |
| Colour fastness to rubbing - wet: | 4-5 (ISO 105-X12)                             |
| Color Fastness To Light:          | 4-5 (ISO 105-B02)                             |
| Seam slippage Warp:               | 1,4 mm (ISO 13936-2)                          |
| Seam slippage Weft:               | 1,0 mm (ISO 13936-2)                          |
| Tensile strength Warp:            | 2100 N (ISO 13934-1)                          |

|                                    |                      |
|------------------------------------|----------------------|
| Tensile strength Weft:             | 1200 N (ISO 13934-1) |
| Tear strength warp:                | 159 N (ISO 13937-1)  |
| Tear Strength weft:                | 85 N (ISO 13937-1)   |
| Dimensional change Warp:           | - 2,0 % (ISO 5077)   |
| Dimensional change Weft:           | 0 % (ISO 5077)       |
| Colour fastness to water wash:     | ISO 105-C06          |
| Staining, multi-fibre :            | 4-5                  |
| Change of colour:                  | 4-5                  |
| Colour fastness to dry cleaning:   | ISO 105-D01          |
| Staining, multi-fibre:             | 4-5                  |
| Change of colour :                 | 4-5                  |
| Colour fastness to waterspottning: | ISO 105-E16          |
| Change of colour :                 | 4-5                  |
| Colour fastness to perspiration:   | ISO 105-E04          |
| Staining, multi-fibre:             | 4-5                  |
| Change of colour:                  | 4-5                  |
| Colour fastness to water:          | 4-5 (ISO 105-E01)    |

