

Select

Select is a phthalate-free synthetic leather that with its soft feel and powerful embossing is very similar to a real leather. It has a wide range of applications and has very good properties. Among other things, it is waterproof, wipeable, abrasion resistant and flameproof. Select is antibacterial and Antimicrobial treated.

It is sold on a scale or in roll with 30 meters.

Suitable for:

Upholstery decoration, Boat & caravan upholstery, Furniture upholstery public environment, Furniture lining, Upholstery marine environment IMO

Width: 1	40 cm ± 2 cm
Content: 7	79% PHTALATE FREE PVC, 21% Cotton
Weight (g/m²):	330 ± 50 g/m ²
Thickness (mm):	,37 mm ± 0,1 mm
Roll length (m):	30
1	3S 5852 Crib 5, BS 5852-1 Source 0 & 1, Cal TB 117, EN 1021-1 & 2, FAR 25.853, IMO 2010 FTP Code Part 8, M2
Martindale:	> 100000 (ISO 5470-2)
Colour fastness to rubbing - dry: ≥	≥ 4-5 (ISO 105-X12)
Colour fastness to rubbing - wet: ≥	≥ 4-5 (ISO 105-X12)

Color Fastness To Light:	≥ 6 (ISO 105-B02)
Tensile strength Warp:	≥ 400 N (ISO 1421)
Tensile strength Weft:	≥ 180 N (ISO 1421)
Tear strength warp:	≥ 20 N (ISO 4674-1)
Tear Strength weft:	≥ 15 N (ISO 4674-1)
Seam slippage Warp:	120 N (ISO 13936-2)
Seam slippage Weft:	120 N (ISO 13936-2)
Adhesion - surface finish Warp:	≥ 15 N (ISO 2411)
Adhesion - surface finish Weft:	≥ 15 N (ISO 2411)

The product is cleaned with lukewarm PH-neutral soapy water and a soft cloth or soft brush. Wipe with a damp cloth afterwards. Do not use solvents or chemical cleaners. Alcoholic disinfectants can dry out the artificial leather. Any stains from ink, wine, coffee, oil, grease and coloring pigments from textiles must be removed immediately.

Please note that Nevotex does not accept complaints due to substandard maintenance or dry folding from jeans and other textiles.

Since this is a PVC product, a water-based contact adhesive should be used when gluing.

Fire test: UFAC Fabric Class 1

Fire test: New York - New Jersey Port Authority

